RSP01

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 24/03/2026 Revision date: 14/06/2026 Supersedes version of: 24/03/2026 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
PRODUCT NAME : RSP01
UFI : F500-W01J-P00D-Q1GU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use,Professional use,Consumer use
Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Automotive Care Products.
Paint remover
Solvents

1.3. Details of the supplier of the safety data sheet

Ribble Technology Ltd
Units 13-14 Ripon Hall Farm,
Catterall Lane,
Catterall, PR3 0PA
United Kingdom
T +44(0)1772 202227
sales@ribbletechnology.co.uk, ribbletechnology.co.uk

1.4. Emergency telephone number

Emergency number : +44(0)1772 202227
English only
Moday - Thursday: 0800 - 1700hrs; Friday: 0800 - 1200hrs.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 1	H314
Skin sensitisation, Category 1	H317

Carcinogenicity Not classified
Specific target organ toxicity (repeated exposure) Not classified
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS05 GHS07

Signal word (CLP) : Danger
Contains : Glycolic acid 70%; Benzyl alcohol

Hazard statements (CLP) : H302+H332 - Harmful if swallowed or if inhaled.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.

Precautionary statements (CLP) : P261 - Avoid breathing mist, spray.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective clothing, eye protection, face protection, protective gloves.
P301+P330+P331+P310 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.
P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor.
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
P312 - Call a POISON CENTRE or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5	≥ 20	Flam. Liq. Not classified Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
water substance with national workplace exposure limit(s) (LV)	CAS-No.: 7732-18-5 EC-No.: 231-791-2	≥ 20 – < 50	Not classified
sodium xylene sulphonate	CAS-No.: 1300-72-7 EC-No.: 701-037-1 REACH-no: 01-2119513350-56	≥ 10 – < 15	Eye Irrit. 2, H319
Glycolic acid 70%	CAS-No.: 79-14-1	≥ 10 – < 15	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Do not remove clothing if it sticks to the skin. Immediately call a POISON CENTRE or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTRE or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : Harmful if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact : Causes severe burns. irritation (itching, redness, blistering).

Symptoms/effects after eye contact : Causes serious eye damage. redness, itching, tears. stinging.

Symptoms/effects after ingestion : Ingestion may cause health problems, including stomach pain, nausea and sickness,diarrhoea. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid fire-fighting water entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Use only outdoors or in a well-ventilated area. Do not breathe mist, spray, vapours.

Hygiene measures : Wash hands, forearms and face thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well-ventilated place away from: Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protection equipment

Personal protective equipment:
Avoid all unnecessary exposure.

Personal protective equipment symbol(s):

Eye and face protection

Eye protection:
Chemical goggles or face shield

Eye protection			
Type	**Field of application**	**Characteristics**	**Standard**
Safety goggles, Safety glasses with side shields	Droplet, mist		EN 166

Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Wear protective gloves.

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves, Reusable gloves	Chloroprene rubber (CR), Butyl rubber		> 0.6		EN ISO 374

Respiratory protection

Respiratory protection:
A suitable particle filter mask is recommended, depending on the expected exposure levels

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
Respiratory protective device with a particle filter	Particle filter	Mist formation, Moist condition, Protection for Liquid particles	

Environmental exposure controls

Other information:
Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Tan.
Appearance	:	Clear liquid.
Odour	:	alcoholic. almond-like.
Odour threshold	:	Not available
Melting point	:	(– 15.4 °C for benzyl alcohol)
Freezing point	:	Not available
Boiling point	:	100 °C (205 °C for benzyl alcohol)
Flammability	:	Non flammable.
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	≥ 100 °C (100 °C for benzyl alcohol)
Auto-ignition temperature	:	(436 °C for benzyl alcohol)
Decomposition temperature	:	Not available
pH	:	2
Viscosity, kinematic	:	Not available
Solubility	:	Soluble. Water: (40 g/L at 25 °C for benzyl alcohol)
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	(7 Pa at 20 °C and 12 Pa at 25 °C °C for benzyl alcohol)
Vapour pressure at 50°C	:	Not available
Density	:	1.05
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapours.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

RSP01	
ATE CLP (oral)	845.07 mg/kg bodyweight
ATE CLP (dust,mist)	5 mg/l/4h

sodium xylene sulphonate (1300-72-7)	
LD50 oral rat	≥ 3346 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), 95% CL: 3196 - 3503
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)

Benzyl alcohol (100-51-6)	
LD50 oral	1620 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
LD50 dermal	2500 mg/kg bodyweight
LC50 Inhalation - Rat	> 4.178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 4178 mg/l

water (7732-18-5)	
LD50 oral rat	90000 mg/kg
LD50 oral	> 90000 mg/kg bodyweight
LD50 dermal	> 90000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns.
pH: 2

water (7732-18-5)	
pH	7

Serious eye damage/irritation : Assumed to cause serious eye damage
pH: 2

water (7732-18-5)	
pH	7

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Additional information : Based on available data, the classification criteria are not met
Germ cell mutagenicity : Not classified
Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified.
Additional information : Based on available data, the classification criteria are not met

sodium xylene sulphonate (1300-72-7)	
NOAEL (chronic, oral, animal/female, 2 years)	≥ 60 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity : Not classified
Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

STOT-repeated exposure : Not classified.
Additional information : Based on available data, the classification criteria are not met

RSP01	
NOAEL (oral, rat, 90 days)	6 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

sodium xylene sulphonate (1300-72-7)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

Benzyl alcohol (100-51-6)	
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:

Aspiration hazard : Not classified
Additional information : Based on available data, the classification criteria are not met

Benzyl alcohol (100-51-6)	
Viscosity, kinematic	4.851 mm²/s

11.2. Information on other hazards

Other information

Potential adverse human health effects and symptoms : Harmful if inhaled.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Not classified

sodium xylene sulphonate (1300-72-7)	
LC50 - Fish [1]	≥ 1580 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1020 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	≥ 758 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Benzyl alcohol (100-51-6)	
LC50 - Fish [1]	460 mg/l
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	230 mg/l waterflea
EC50 - Other aquatic organisms [2]	500 mg/l

Benzyl alcohol (100-51-6)	
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	76.828 mg/l Test organisms (species): other:
NOEC chronic fish	48.897 mg/l Test organisms (species): other: Duration: '30 d'

12.2. Persistence and degradability

RSP01	
Persistence and degradability	Not established.

sodium xylene sulphonate (1300-72-7)	
Persistence and degradability	Rapidly degradable

Glycolic acid 70% (79-14-1)	
Persistence and degradability	Rapidly degradable

Benzyl alcohol (100-51-6)	
Persistence and degradability	Rapidly degradable

water (7732-18-5)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

RSP01	
Bioaccumulative potential	Not established.

Benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1

water (7732-18-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.38

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

RSP01	
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Ecological waste information : Avoid release to the environment.

HP Code : HP6 - “Acute Toxicity:” waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
HP8 - “Corrosive:” waste which on application can cause skin corrosion.
HP13 - “Sensitising:” waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3265	UN 3265	UN 3265	UN 3265	UN 3265
14.2. UN proper shipping name				
CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%)	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%)	Corrosive liquid, acidic, organic, n.o.s. (Glycolic acid 70%)	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%)	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%)
Transport document description				
UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%), 8, II, (E)	UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%), 8, II	UN 3265 Corrosive liquid, acidic, organic, n.o.s. (Glycolic acid 70%), 8, II	UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%), 8, II	UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Glycolic acid 70%), 8, II
14.3. Transport hazard class(es)				
8	8	8	8	8
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-A EmS-No. (Spillage): S-B	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : C3
Special provisions (ADR) : 274
Limited quantities (ADR) : 0
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P001

Mixed packing provisions (ADR)	:	MP8, MP17
Portable tank and bulk container instructions (ADR)	:	T14
Portable tank and bulk container special provisions (ADR)	:	TP2, TP27
Tank code (ADR)	:	L10BH
Vehicle for tank carriage	:	AT
Transport category (ADR)	:	1
Special provisions for carriage - Operation (ADR)	:	S20
Hazard identification number (Kemler No.)	:	88
Orange plates	:	
Tunnel restriction code (ADR)	:	E
EAC code	:	2X
APP code	:	B

Transport by sea

Special provisions (IMDG)	:	274
Limited quantities (IMDG)	:	0
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P001
Tank instructions (IMDG)	:	T14
Tank special provisions (IMDG)	:	TP2, TP27
Stowage category (IMDG)	:	B
Stowage and handling (IMDG)	:	SW2
Segregation (IMDG)	:	SGG1, SG36, SG49
Properties and observations (IMDG)	:	Causes burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Forbidden
PCA limited quantity max net quantity (IATA)	:	Forbidden
PCA packing instructions (IATA)	:	850
PCA max net quantity (IATA)	:	0.5L
CAO packing instructions (IATA)	:	854
CAO max net quantity (IATA)	:	2.5L
Special provisions (IATA)	:	A3, A803
ERG code (IATA)	:	8L

Inland waterway transport

Classification code (ADN)	:	C3
Special provisions (ADN)	:	274
Limited quantities (ADN)	:	0
Excepted quantities (ADN)	:	E0
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP, EP
Number of blue cones/lights (ADN)	:	0

Rail transport

Classification code (RID)	:	C3
Special provisions (RID)	:	274
Limited quantities (RID)	:	0
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P001
Mixed packing provisions (RID)	:	MP8, MP17
Portable tank and bulk container instructions (RID)	:	T14
Portable tank and bulk container special provisions (RID)	:	TP2, TP27
Tank codes for RID tanks (RID)	:	L10BH
Special provisions for RID tanks (RID)	:	TU38, TE22
Transport category (RID)	:	1

Hazard identification number (RID) : 88

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

France

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. Not classified	Flammable liquids Not classified
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1B	Skin sensitisation, category 1B
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.